



CARE AND MAINTENANCE OF SIERRASOLID SURFACE TABLETOPS

CLEANING – To clean, use soap and water—apply with a sponge and towel dry to eliminate water spots. For stubborn stains, use a bleaching, nonabrasive cleaner such as Soft Scrub.

DISINFECTING – Wipe surface with diluted household bleach [equal parts of household bleach and water]. Rinse with water and wipe dry with a towel.

CHEMICALS – SierraSolid tabletops are very resistant to most household cleaners but should not be exposed to industrial type cleaners such as paint remover, paintbrush cleaners, metal cleaners, oven cleaners, acetones, nail polish removers and acid drain cleaners. Protect finish with acrylic wax such as Countertop Magic available at home improvement stores.

RENEWING GRANITZ [SEMI-GLOSS] AND TRANSLUCENTS [MATTE FINISH]:

On the Translucent SierraSolids, light scratches can be removed with a 3M Gray Scotch Brite pad. Then wipe down with soap and water and towel dry. On the Granitz, then use an acrylic polish [such as Countertop Magic] to return it to its original finish.

Deep scratches can be removed by sanding prior to the buffing process outlined above but may require the services of a professional to ensure the sanding is properly blended with the buffing. Refer to the Solid Surface Fabricators Association website at <http://www.fabricatordirectory.com/> to locate a professional near you.

RENEWING ALUMISTONE AND QUARTZSTONE [BOTH GLOSS FINISH]:

Due to the gloss finish on these two series, light or deep scratches will require the services of a professional. Refer to the Solid Surface Fabricators Association website at <http://www.fabricatordirectory.com/> to locate a professional near you. Maintain luster with the use of a solid surface acrylic polish after buffing process is complete.

MTS Seating
7100 Industrial Drive
Temperance, MI 48182

t: 734-847-3875
f: 800-329-0687
w: mtsseating.com



w: theartofseating.com